

PRODUCT DATA

NR.1 GREEN PAINT STRIPPER

DESCRIPTION

RUST-OLEUM® Nr. 1 Green Paint Stripper is a highly effective paint dissolving/lifting material without methylene chloride.

RECOMMENDED USES

RUST-OLEUM® Nr. 1 Green Paint Stripper can be used for a quick removal of layers of old paint and glue.

RUST-OLEUM® Nr. 1 Green Paint Stripper is developed to remove all types of oil- and alkyd-based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden surfaces.

RUST-OLEUM® Nr. 1 Green Paint Stripper does not contain methylene chloride, NMP, acids, alkali's, biocides and conservation additives. It will not affect metal, mineral or wooden substrates.

TECHNICAL DATA

Appearance: Clear, thixotropic layer

Composition: Special blend of solvents and paraffin wax

VOC-content: 900 g/l

Coverage

Theoretical: 250 - 500 g/m² ≈ 2 - 4 m²/l.

Practical: Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

DIRECTION FOR USE

Remove loose coatings as much as possible by scraping.

To release possible pressure open the can carefully.

Apply RUST-OLEUM® Nr. 1 Green Paint Stripper thickly in an even layer with a brush (disposable brush, flat or round). Do not use synthetic brushes.

Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper.

Thick layers of some (two-component) products may need an additional treatment.

After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water and allow to dry completely before applying a coating.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 25°C and relative humidity below 85%.

REMARKS

RUST-OLEUM RUST-OLEUM® Nr. 1 Green Paint Stripper may affect plastic materials alike e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

SAFETY

Do not use in the immediate vicinity of flames, hot surfaces or welding works.

No smoking. Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

1 year from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 25°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu