# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 28 December 2017 Version : 16.07



# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: NOVAGUARD 200/840 HARDENER
Product code	: 00253797
Other means of identification	: Not available.
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
<ul> <li>1.3 Details of the supplier of PPG Coatings SPRL/BVBA Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435</li> <li>e-mail address of person responsible for this SDS</li> </ul>	f the safety data sheet : PMC.Safety@PPG.com
1.4 Emergency telephone n Supplier Telephone number +31 20 4075210	umber :
131 20 4073210	

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00253797 NOVAGUARD 200/840 HARDENER Date of issue/Date of revision

: 28 December 2017

## **SECTION 2: Hazards identification**

2.2 Label elements		
Hazard pictograms		
Signal word	Danger	
Hazard statements	Toxic in contact with skin or if inhaled. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	$\mathbf{W}$ ear protective gloves. Wear protective clothing. Wear eye or face protection. Avoid breathing vapour.	
Response	<b>I</b> NHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or physician. IF ON SKIN hair): Take off immediately all contaminated clothing. Rinse skin with water. IF I EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.	(or IN
Storage	Store locked up.	
Disposal	Not applicable. ₱280, P261, P304 + P340, P301 + P310, P303 + P361 + P353, P305 + P351 + P P405	<b>2</b> 338,
Hazardous ingredients	?2'-dimethyl-4,4'-methylenebis(cyclohexylamine) N-(3-(trimethoxysilyl)propyl)ethylenediamine 2,4,6-tris(dimethylaminomethyl)phenol	
Supplemental label elements	Not applicable.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.	
Special packaging requirem Containers to be fitted with child-resistant fastenings	nts Not applicable.	
Tactile warning of danger	Not applicable.	
2.3 Other hazards		
Other hazards which do not result in classification	None known.	

Code : 00253797 NOVAGUARD 200/840 HARDENER Date of issue/Date of revision

: 28 December 2017

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures :	Mixture			
			<b>Classification</b>	
Product/ingredient name	Identifiers	% by weight	Regulation (EC) No. 1272/2008 [CLP]	Туре
2,2'-dimethyl-4,4'-methylenebis (cyclohexylamine)	EC: 229-962-1 CAS: 6864-37-5 Index: 612-110-00-1	≥75 - ≤90	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤24	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1]
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC: 217-164-6 CAS: 1760-24-3	≥1.0 - ≤5.0	Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
2,4,6-tris(dimethylaminomethyl) phenol	EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤3.6	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317	[1]
proprietary 2-methyl-4, 4'methylenebis(cyclohexylamine)	CAS: SUB132924	≤0.29	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 2, H373 (adrenal, blood, heart, kidneys, liver) Aquatic Chronic 2, H411	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

Code	: 00253797	Date of issue/Date of revision	: 28 December 2017
NOVAGUAR	D 200/840 HARDENER		

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention. : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is Inhalation irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. : No action shall be taken involving any personal risk or without suitable training. If it is Protection of first-aiders suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Eye contact	: Causes serious eye damage.
Inhalation	: Toxic if inhaled.
Skin contact	: Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
Over-exposure signs/	<u>symptoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	<ul> <li>Adverse symptoms may include the following: stomach pains</li> </ul>

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

#### 5.2 Special hazards arising from the substance or mixture

Code : 00253797 NOVAGUARD 200/840 HARD	Date of issue/Date of revision         : 28 December 2017           NER
SECTION 5: Firefigh	ng measures
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. The material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
5.3 Advice for firefighters	
Special precautions for fire fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitabl training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for c	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Code : 00253797 Date of issue/Date of revision

: 28 December 2017

**NOVAGUARD 200/840 HARDENER** 

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

No exposure limit value known.

Code : 00253797 NOVAGUARD 200/840 HARDENER Date of issue/Date of revision

: 28 December 2017

**SECTION 8: Exposure controls/personal protection** 

#### **DNELs**

DNELs - Not available.

#### **PNECs**

PNECs - Not available.

8.2 Exposure controls		
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measu	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles and face shield. Use eye protection according to EN 166.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.
Gloves	:	nitrile neoprene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code	: 00253797	Date of issue/Date of revision	: 28 December 2017
NOVAGUAR	D 200/840 HARDENER		

# **SECTION 9: Physical and chemical properties**

	• •			
9.1 Information on basic physical and chemical properties				
<u>Appearance</u>				
Physical state	: Liquid.			
Colour	: Black.			
Odour	: Amine-like. [Strong]			
Odour threshold	: Not available.			
рН	: insoluble in water.			
Melting point/freezing point	: May start to solidify at the following temperature: -7.1°C (19.2°F) This is based on data for the following ingredient: 2,2'-dimethyl-4,4'-methylenebis (cyclohexylamine). Weighted average: -8.54°C (16.6°F)			
Initial boiling point and boiling range	: >37.78°C			
Flash point	: Closed cup: 105°C			
Evaporation rate	: 0.007 (benzyl alcohol) compared with butyl acetate			
Material supports combustion.	: Yes.			
Flammability (solid, gas)	: liquid			
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)			
Vapour pressure	: Highest known value: 0.04 kPa (0.3 mm Hg) (at 20°C) (N-(3-(trimethoxysilyl) propyl)ethylenediamine). Weighted average: 0.004 kPa (0.03 mm Hg) (at 20°C)			
Vapour density	: Highest known value: 3.7 (Air = 1) (benzyl alcohol).			
Relative density	: 0.97			
Solubility(ies)	: Insoluble in the following materials: cold water.			
Partition coefficient: n-octanol/ water	: Not applicable.			
Auto-ignition temperature	: 426°C			
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).			
Viscosity	: Kinematic (40°C): <0.14 cm²/s			
Explosive properties	: Product does not present an explosion hazard.			
Oxidising properties	: Product does not present an oxidizing hazard.			

#### 9.2 Other information

No additional information.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830							
Code <th::< th="">: 00253797Date of issue/Date of revision: 28 December 2017NOVAGUARD 200/840 HARDENER</th::<>							
SECTION 10: Stabilit	SECTION 10: Stability and reactivity						
<b>10.5 Incompatible materials</b> : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.							
10.6 Hazardous	: Depending on co	onditions, decomposition products may	v include the following				

10.6 Hazardous decomposition products

Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

# **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	LC50 Inhalation Dusts and mists	Rat	420 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-
2	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### Acute toxicity estimates

Route	ATE value	
Øral	583.3 mg/kg	
Dermal	373.2 mg/kg	
Inhalation (vapours)	67.48 mg/l	
Inhalation (dusts and mists)	0.6092 mg/l	

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
₽,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

#### **Conclusion/Summary**

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Eyes Respiratory

Skin

: There are no data available on the mixture itself.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
₹,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitising

#### Conclusion/Summary

- : There are no data available on the mixture itself.
- Respiratory

Skin

: There are no data available on the mixture itself.

ry : There are no data available on the mixit

Code	: 00253797	Date of issue/Date of revision	: 28 December 2017
NOVAGUAR	D 200/840 HARDENER		

# **SECTION 11: Toxicological information**

<u>Mutagenicity</u>		
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.	
<b>Carcinogenicity</b>		
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.	
Reproductive toxicity		
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.	
<b>Teratogenicity</b>		
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.	
Specific target organ toxicity (single exposure)		
Not available.		

#### Specific target organ toxicity (repeated exposure)

Product/ing	redient name	Category	Route of exposure	Target organs
proprietary 2-methyl-4,4'meth	ylenebis(cyclohexylamine)	Category 2	Not determined	adrenal, blood, heart, kidneys and liver
Aspiration hazard				
Not available.				
Information on likely routes of exposure	: Not available.			
Potential acute health effect	<u>s</u>			
Inhalation	: Toxic if inhaled.			
Ingestion	: Harmful if swallowed.			
Skin contact	: Causes severe burns. To	oxic in contact with s	kin. May cause an	allergic skin reaction.
Eye contact	: Causes serious eye dama	age.		
Symptoms related to the phy	ysical, chemical and toxicol	ogical characteris	<u>tics</u>	
Inhalation	: No specific data.			
Ingestion	: Adverse symptoms may include the following: stomach pains			
Skin contact : Adverse symptoms may include the following: pain or irritation redness blistering may occur				
Eye contact : Adverse symptoms may include the following: pain watering redness				
Delayed and immediate effe	cts as well as chronic effect	ts from short and	long-term exposu	<u>re</u>
Short term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
<u>Long term exposure</u>				
Potential immediate : Not available. effects				
Potential delayed effects	Potential delayed effects : Not available.			
Potential chronic health effe				
				40/4/

English (GB)

Code	: 00253797	Date of issue/Date of revision	: 28 December 2017
NOVAGUA	RD 200/840 HARDENER		

### **SECTION 11: Toxicological information**

1	Not	avai	labl	~	
I	NOU	avai	lapie	э.	

Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Other information	: Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, 2,4,6-tris(dimethylaminomethyl)phenol. May produce an allergic reaction.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
penzyl alcohol	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2,2'-dimethyl-4,4'-	2.5	-	low
methylenebis (cyclohexylamine)			
benzyl alcohol	1.1	-	low

#### 12.4 Mobility in soil

Soil/water partition	
coefficient (Koc)	
Mobility	

: Not available.

: Not available.

Code : 00253797 **NOVAGUARD 200/840 HARDENER**  Date of issue/Date of revision

: 28 December 2017

### SECTION 12: Ecological information

# 12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

#### 12.6 Other adverse effects : No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11* waste paint and varnish containing organic solvents or other hazardous subst	
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging
Special precautions	taken wher Empty cont	al and its container must be disposed of in a safe way. Care should be a handling emptied containers that have not been cleaned or rinsed out. ainers or liners may retain some product residues. Avoid dispersal of al and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	2922	2922	2922	2922
14.2 UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
	<ul> <li>2',2'-dimethyl-4,4'-</li> <li>methylenebis</li> <li>(cyclohexylamine), 2,4,</li> <li>6-tris</li> <li>(dimethylaminomethyl)</li> <li>phenol)</li> </ul>	<ul> <li>2'-dimethyl-4,4'-</li> <li>methylenebis</li> <li>(cyclohexylamine), 2,4,</li> <li>6-tris</li> <li>(dimethylaminomethyl)</li> <li>phenol)</li> </ul>	<ul> <li>2'-dimethyl-4,4'- methylenebis</li> <li>(cyclohexylamine), 2,4,</li> <li>6-tris</li> <li>(dimethylaminomethyl)</li> <li>phenol)</li> </ul>	<ul> <li>2'-dimethyl-4,4'-</li> <li>methylenebis</li> <li>(cyclohexylamine), 2,4,</li> <li>6-tris</li> <li>(dimethylaminomethyl)</li> <li>phenol)</li> </ul>
14.3 Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)	8 (6.1)
14.4 Packing group	II	II	II	II
English (GE	3)	United Kingdom	(UK)	12/15

Code : 00253 NOVAGUARD 200/84	3797	(REACH), Annex II, as a Date of issue/Da		28 December 2017	
14. Transport					
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.	
Marine pollutant substances	Not applicable.	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.	
		ardous substance mark is	s not required when trans	sported in sizes of ≤5 L	
	The environmentally haz or ≤5 kg.	ardous substance mark is	s not required when trans	sported in sizes of ≤5 L	
	•	rk is not required when tra	ansported in sizes of ≤5 I	L or ≤5 kg.	
	The environmentally haze regulations.	ardous substance mark r	nay appear if required by	other transportation	
14.6 Special precauti user	upright and	within user's premises: secure. Ensure that pers an accident or spillage.			
14.7 Transport in bul according to Annex I Marpol and the IBC C	lof	ble.			
SECTION 15: R	Regulatory inforn	nation			
15.1 Safety, health ar	nd environmental regul	ations/legislation speci	fic for the substance o	r mixture	
	No. 1907/2006 (REACH				
	substances subject to	authorisation			
<u>Annex XIV</u>					
None of the compo					
Substances of ve					
None of the compo					
Annex XVII - Restri on the manufactur		DIE.			
placing on the mar	rket and				
use of certain dang substances, mixtu					
articles					
Other EU regulation	<u>IS</u>				
Ozone depleting substances (1005/2009/EU) Not listed.					
<u>Seveso Directive</u>					
	This product is controlled under the Seveso Directive.				
Danger criteria	•				
Category					
H2: Acute toxicity E2: Hazardous to 2: Toxic	H2: Acute toxicity 2 any route of entry or Acute toxicity 3 Inhalation route of entry E2: Hazardous to the aquatic environment - Chronic 2 2: Toxic				
9ii: Toxic for the e	nvironment				
English (GB	3)	United Kingdom	(UK)	13/15	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Code : 00253797 NOVAGUARD 200/840 HARDENER Date of issue/Date of revision

: 28 December 2017

**SECTION 15: Regulatory information** 

# 15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Acute Tox. 3, H311	Calculation method
Acute Tox. 3, H331	Calculation method
Skin Corr. 1A, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

#### Full text of abbreviated H statements

<b>H</b> 302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Code : 00253797 NOVAGUARD 200/840 HARDENER	Date of issue/Date of revision	: 28 December 2017
SECTION 16: Other information		

Acute Tox. 2, H330	ACUTE TOXICITY (inhalation) - Category 2
Acute Tox. 3, H311	ACUTE TOXICITY (dermal) - Category 3
Acute Tox. 3, H331	ACUTE TOXICITY (inhalation) - Category 3
Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1A, H314	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C, H314	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1, H317	SKIN SENSITISATION - Category 1
Skin Sens. 1B, H317	SKIN SENSITISATION - Category 1B
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE
	- Category 2

#### **History**

Date of issue/ Date of revision	: 28 December 2017
Date of previous issue	: 14 July 2017
Prepared by	: EHS
Version	: 16.07
<b>_</b>	

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.