

# ANDCOAT GRAFFI CLEAN 300

**andrews**  
COATINGS LTD

## PRODUCT DESCRIPTION

Graffi Clean 300 is a viscous graffiti remover for use on masonry surfaces. It is a gelled remover which will cling to the surface.

## ADVANTAGES

Fast acting and effective on most masonry surfaces

## PRE-TESTING

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

## SHELF LINE

Graffi Clean 300 may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

## AVERAGE SPREAD RATE

Concrete - 2-4m<sup>2</sup>/pl  
Marble Polished - 3-6m<sup>2</sup>/pl  
Marble unpolished- 2-5m<sup>2</sup>/pl  
Granite Polished - 3-6m<sup>2</sup>/pl  
Granite Unpolished - 2-5m<sup>2</sup>/pl  
Sandstone- Unpolished - 3-6m<sup>2</sup>/pl  
Slate - Unpolished- 2-5m<sup>2</sup>/pl  
Fired Clay- Brick - 2-4m<sup>2</sup>/pl  
Fired Clay Tile- 3-6m<sup>2</sup>/pl  
Fired Clay terracotta 3-6m<sup>2</sup>/pl  
Fired Clay Pavers 3-6m<sup>2</sup>/pl

Please note these are average spread rates and this could change depending on the surface profile. For more information please contact the Andrews Coatings team.

## APPLICATION INSTRUCTIONS

1. Apply with brush, airless sprayer or roller for large areas.
2. Leave to penetrate for 15 – 60 minutes. With low outside temperatures, longer dwell times may be necessary. Avoid applying to surface temperatures below 50°C.
3. Can be used on wet or damp surfaces.
4. Wash off with high pressure (60 – 150 bar, 10-20 litres per minute, depending on surface & conditions), 90°C hot water will help removal.
5. If ghosting remains on the surface, use Graffi Ghost and Graffi Rinse.

**Please Note:** Never use higher pressure than the surface can tolerate.

Extend penetration time when using lower pressure. High pressure washer with high flow rate of 15-30 litres per minute will also aid removal and compensate for lower pressure.

## SAFETY INFORMATION

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

## EQUIPMENT

Apply with a solvent resistant brush, airless sprayer or roller.

## COVERAGE RATES

Coverage rates will vary according to the character of the surface.

## Contact info:

INFO@ANDREWSCOATINGS.CO.UK  
01902 710057

If you need any further information please feel free to contact a member of our technical team where we will be happy to assist.