

OFF THE WALL GRAFFITI PROTECTOR



PRODUCT DESCRIPTION

OTWGP is a specially formulated single pack external coating designed to give effective protection against both fly-posting and graffiti.

RAL Colours also available.

APPLICATION

By brush/roller or spray.

Apply in one heavy coat.

Do not apply too thin.

Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

GRAFFITI REMOVAL

Graffiti should be removed using warm soapy water. If using a pressure washer, no more than 70 bar should be used.

EQUIPMENT CARE

All equipment should be cleaned with white spirit.

STORAGE

Store away from direct sunlight and sources of heat. Protect from frost. Do not allow moisture into the can.

COVERAGE

One coat @ 8m²/Litre

WTF-125 Microns

DFT- 95 Microns

DRYING TIMES

Touch Dry: 1-2 hours

Full Cure: 6 Hours

PREPARATION

Ensure surfaces to be treated are clean, free from contamination and dry. To prevent concrete surfaces darkening, it is advisable to first apply a primer/sealer of Andcoat WB Concrete sealer.

ADVANTAGES

A one coat application where graffiti will not adhere to the surface, once dry, graffiti can be removed easily by using warm soapy water.

No reapplication required.

USES

Most surfaces can be protected with just one coat Of OTWGP, giving quick application and protection from Graffiti and fly posting.

COLOUR RANGE

Clear Gloss or Clear Semi Matt

PACK SIZE

Single component product, supplied in 5 litre cans.

VOLUME SOLIDS:

75%

SHELF LIFE

12 months (in original sealed container.)

Contact info:

INFO@ANDREWSCOATINGS.CO.UK

01902 710057

If you need any further information please feel free to contact a member of our technical team where we will be happy to assist.