

## PRODUCT DATA

## FASSICLOR

### DESCRIPTION

Solvent borne chlorinated rubber paint.

### MAIN PROPERTIES

Alkali and acid resistant - excellent water resistance - U.V. stable.

### RECOMMENDED USES

Decorative painting of swimming pools or ponds in concrete.

### TECHNICAL DATA

Appearance:	Satin gloss (gloss 60°): $\pm 47\%$
Colour:	White, azure blue, water green, pearl grey
Density:	1.2 - 1.3 g/cm <sup>3</sup>
Solids Content:	In volume: 28 - 33%
	In weight: 49 - 56%
Recommended film thickness:	Wet film: $\pm 165$ micron (cons.: 6 m <sup>2</sup> /l)
	Dry film: $\pm 50$ micron (cons.: 6 m <sup>2</sup> /l)
VOC-content:	Max. 640 g/l
Flashpoint:	> 39°C

### Drying times 20°C/50% r.h.

To touch:	1½ hours
To handle:	3 hours
To recoat:	24 hours
Full hardness	12 days

### Coverage

Theoretical:	2 coats of $\pm 6$ m <sup>2</sup> /l per coat
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Apply without priming coat on old chlorinated rubber paint (after cleaning) or on a hardened and dry concrete substrate (maximum humidity degree 5%). Attention: since Fassiclor is not a waterproofing product, the concrete substrate must be waterproof!

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

### APPLICATION & THINNING

Brush:	If necessary, dilute slightly with Thinner 22.
Roller:	Apply the first coat with brush by preference, if necessary dilute slightly with Thinner 22.
Air-atomised spray:	If necessary, dilute slightly with Thinner 22.
Airless spray:	Dilute with $\pm 10 - 20\%$ Thinner 22. Nozzle: 018 / Pressure: 200 bars.
Cleanup:	Thinner 22

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

## PRODUCT DATA

## FASSICLOR

### APPLICATION CONDITIONS

Apply in a dry and well-ventilated area.

### REMARKS

When using in indoor swimming pools, especially during airless spraying, it is advisable to wear a mask due to limited ventilation.

Swimming pools and other under water applications have to dry/cure for minimal 14 days before they can be immersed with water. Early contact with water can cause premature fading, chalking and blistering.

Old coatings: only apply on perfectly sound similar and compatible paints (test in case of doubt).

Building design of pool must be in accordance with specific construction rules.

Water chemistry balance must be respected (Ph, water hardness, alkalinity etc).

Any specific water treatment (salt, ozone, etc.) must be checked to avoid impact on coating system. A swimming pool specialist should be consulted for further information before applying any coating system.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

#### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)