



Paints, Primers and Specialist Coatings

## SAFETY DATA SHEET

### 132/Q265 - FLOORPACK - BASE

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name 132/Q265 - FLOORPACK - BASE

Product number 132/Q265/1 - BASE

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT Crack and hole filler

##### 1.3. Details of the supplier of the safety data sheet

###### Supplier

COO-VAR  
Lockwood Street  
Hull  
HU2 0HN  
+44 (0) 1482 328053(T)  
+44 (0) 1482 219266(F)  
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Eye Irrit. 2 - H319

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43. R52/53.

Human health The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Physicochemical When handled correctly, undamaged units represent no danger.

##### 2.2. Label elements

###### Pictogram



Signal word Warning

## 132/Q265 - FLOORPACK - BASE

<b>Hazard statements</b>	<p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>EUH205 Contains epoxy constituents. May produce an allergic reaction.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P313 Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container to ...</p>
<b>Contains</b>	<p>REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW&lt;=700), FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL, OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS</p>
<b>Supplementary precautionary statements</b>	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337 If eye irritation persists:</p> <p>P362 Take off contaminated clothing.</p> <p>P363 Wash contaminated clothing before reuse.</p> <p>P321 Specific treatment (see medical advice on this label).</p>

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)		10-30%
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0006
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

**132/Q265 - FLOORPACK - BASE**

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL			1-5%
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-2119454392-40-0003	
<b>Classification</b> Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi;R38. N;R51/53. R43.		
Titanium Dioxide			1-5%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-xxxx	
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -		
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS			1-5%
CAS number: 68609-97-2	REACH registration number: 01-2119485289-22-0005		
<b>Classification</b> Skin Irrit. 2 - H315 Skin Sens. 1 - H317	<b>Classification (67/548/EEC or 1999/45/EC)</b> R43 Xi;R38		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

**4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

**4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## 132/Q265 - FLOORPACK - BASE

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Non flammable at room temperature, but will burn. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Toxic gases or vapours.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## 132/Q265 - FLOORPACK - BASE

**Usage description** Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **Titanium Dioxide**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

WEL = Workplace Exposure Limit

#### REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700) (CAS: 25068-38-6)

**DNEL** Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day  
 Workers - Inhalation; Long term systemic effects: 12.25 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 8.33 mg/kg/day  
 Workers - Inhalation; Short term systemic effects: 12.25 mg/m<sup>3</sup>  
 Consumer - Oral; Long term systemic effects: 0.75 mg/kg/day  
 Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 3.571 mg/kg/day

**PNEC** - Fresh water; Long term 0.006 mg/l  
 - Sediment (Freshwater); Long term 0.996 mg/l  
 - STP; Long term 10 mg/l  
 - Soil; Long term 0.196 mg/l  
 - Marine water; 0.0006 mg/l  
 - Sediment (Marinewater); 0.0996 mg/l  
 - Water; 0.0018 mg/l

#### FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

**DNEL** Workers - Inhalation; Long term systemic effects: 29.39 mg/kg  
 Workers - Dermal; Long term systemic effects: 104.15 mg/kg/day  
 General population - Inhalation; Long term systemic effects: 8.7 mg/kg  
 General population - Dermal; Long term systemic effects: 62.5 mg/kg/day  
 General population - Oral; Long term systemic effects: 6.25 mg/kg/day

#### Titanium Dioxide (CAS: 13463-67-7)

**DNEL** Industry - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>  
 Consumer - Oral; Long term systemic effects: 700 mg/kg/day

**PNEC** - Fresh water; 0.184 mg/l  
 - Marine water; 0.0184 mg/l  
 - Sediment (Freshwater); >=1000 mg/kg  
 - Sediment (Marinewater); >=100 mg/kg  
 - Soil; 100 mg/kg  
 - STP; 100 mg/kg

#### 8.2. Exposure controls

## 132/Q265 - FLOORPACK - BASE

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

### Personal protection

Unprotected persons should be kept away from treated areas.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

### Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

### Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Granules. Coloured paste.
Colour	White / off-white.
Odour	Sweetish.
Initial boiling point and range	>150°C @ 760 mm Hg
Vapour pressure	<0.1 mbar @ °C
Relative density	1.12 @ @ 25 C°C
Solubility(ies)	Immiscible with water
Auto-ignition temperature	>200°C
Viscosity	90 Pas @ 25 C°C

### 9.2. Other information

Volatility	0
Volatile organic compound	This product contains a maximum VOC content of 0 g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

### 10.2. Chemical stability

## 132/Q265 - FLOORPACK - BASE

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not occur

### 10.4. Conditions to avoid

**Conditions to avoid** Not known.

### 10.5. Incompatible materials

**Materials to avoid** Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** No specific health hazards known.

**Inhalation** May cause respiratory system irritation.

**Ingestion** Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

**Skin contact** Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritating to eyes.

**Acute and chronic health hazards** May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

**Route of entry** Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

**Medical considerations** Skin disorders and allergies.

**Toxicological information**

## SECTION 12: Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product.

### 12.1. Toxicity

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** The product is non-volatile.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## 132/Q265 - FLOORPACK - BASE

**Other adverse effects** Not determined.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning
<b>Waste class</b>	When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

#### 14.1. UN number

**UN No. (ADR/RID)** 3082

**UN No. (IMDG)** 3082

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (IMDG)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ICAO)** PAINT OR PAINT RELATED MATERIAL

**Proper shipping name (ADN)** PAINT OR PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)


**ADR/RID class** 9

**ADR/RID subsidiary risk** HAZARD ID 90

**IMDG class** 9

**ICAO class/division** 9

#### Transport labels



#### 14.4. Packing group

**ADR/RID packing group** III

**IMDG packing group** III

**ICAO packing group** III



**132/Q265 - FLOORPACK - BASE****14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

**14.6. Special precautions for user**

EmS F-A S-F

Tunnel restriction code (E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.  
CHIP for everyone HSG228.  
Safety Data Sheets for Substances and Preparations.  
Approved Classification and Labelling Guide (Sixth edition) L131.  
Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information**

**Revision comments** Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Revisions to Sections (2),(3),(8),(15), and (16) - re-classification of resin components.

**Issued by** Technical Dept. (P.E.)**Revision date** 14/05/2015**Revision** 4**Supersedes date** 04/12/2012**SDS number** 10834**SDS status** Approved.**Signature** Initials \_\_\_\_\_

## 132/Q265 - FLOORPACK - BASE

**Risk phrases in full**

Not classified.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Hazard statements in full**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.