



Andrews Coatings Ltd
Carver Buildings, Littles Lane
Wolverhampton,
West Midlands
WV1 1JY

How to apply kitchen wall paint

Application: Stir thoroughly prior to use. The product may be applied by brush or medium pile roller.

Coverage: Up to 12m²/l per coat. Coverage may vary depending upon method and rate of application and porosity of surface.

Drying Time: Touch dry in 2 hours. Apply a second coat after 2 hours if necessary. Hard dry in 4 hours, full hardness achieved after 7 days.

Clean Up: Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Limitations: For interior use only. Temperature at time of the application and during drying should be greater than 5°C. To ensure paint suitability for your particular project test on a small inconspicuous area first.

Perfectly paired with Kitchen Cupboard Paint and Kitchen Tile Paint

Pair Rust-Oleum Kitchen Wall Paint with our Kitchen Cupboard Paint, and Kitchen Tile Paint. Create a coordinated kitchen with complementary colours for your cabinets and wall tiles.

Instil a sense of harmony and blend seamlessly by painting your kitchen cabinets the same shade as your walls; or add a pop of colour to your tiles for a striking accent.

 01902 710057  andrewscoatings.co.uk  info@andrewscoatings.co.uk



@andrewscoatings